

Main Features

- Support 4x4 MIMO for n78 and 2x2 MIMO for band 1/3
- Support 3G, 4G and 5G technologies
- Suitable for large-scale indoor installations / Neutral Host / Multi-Operator applications
- Hybrid DC/Fiber Feed for plug and play installation
- Features remote-control and monitoring



Electrical Specifications

		Uplink	Downlink
Frequency	Band 1 (2x2 MIMO)	1920 - 1980 MHz	2110 - 2170 MHz
	Band 3 (2x2 MIMO)	1710 - 1785 MHz	1805 - 1880 MHz
	n78 (4x4 MIMO)	3300 - 3600 MHz	3300 - 3600 MHz
Instantaneous bandwidth	n78 (4x4 MIMO)	300 MHz	300 MHz
Gain	Band 1/3	31 ± 2 dB	31 ± 2 dB
	n78	34 ± 2 dB	34 ± 2 dB
RF output power	Band 1/3	---	24 ± 1 dBm (RF per port per band)
	n78	---	27 ± 1 dBm (RF per port)
Antenna gain		3 dBi @ 1.7-2.7GHz	3 dBi @ 1.7-2.7GHz
		5 dBi @ 3.3-3.8GHz	5 dBi @ 3.3-3.8GHz
Optical output power		5 ± 2 dBm	---
Optical wavelength		1310 nm	1550 nm
Gain control range		15 dB / 1 dB step	15 dB / 1 dB step
Max. non-destructive input power		-10 dBm	---
Impedance		50 Ω	50 Ω
Power supply		40 - 57 VDC	

Environmental Specifications

Operating temperature range	-10 °C to +45 °C
Storage temperature range	-40°C to +85°C
Relative humidity	10% - 95%
Ingress protection	IP50

Mechanical Specifications

Optical connector	4 x SC/APC (4x4 MIMO port)
Installation	Ceiling, wall or pole mounted
Antenna	Omni antenna Integrated

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.