

- High grade copper wire
- CU/XLPE/CCABS/LSZH
- Class 5 flexible conductor
- Rated voltage: 0.6/1kV
- Rated temperature: 90°C
- This product used for power transmission




Photo for reference

Part number

PW2XHK-S2-2C <u>XX</u> mm2- <u>X</u>	Shielded power cable, 2 cores
1 2	
*1 indicate the single core section area	
*2 indicate the insulation colour, the meaning of the numbers is in the "colour code" table.	

For example:

Part No.	Description
PW2XHK-S2-2C16mm2-2	2x16mm ² , Class 5, Blue and Black XLPE insulation, Copper clad aluminium wire braiding, Black LSZH sheath

Colour code

Insulation colour: The meaning of the number is as below.

Number	0	1	2	3	4	5	6
Colour	Red, Blue	Blue, Brown	Blue, Black	Blue, Grey	Black, Grey	Red, Black	Black, White
Sheath colour: Black							

Material and dimension

No.	Item		PW2XHK-S2-2CXXmm2-X
1	Conductor	Material	Annealed bare copper, IEC 60228 class 5
		Quantity	2 cores
2	Insulation	Material	XLPE
3	Filler	Material	Optional
4	Tape	Material	Optional
5	Shield	Material	Copper clad aluminium wire braid
		Coverage	≥80%
6	Sheath	Material	LSZH

Noted: For larger cross section conductor, tape may also be used around conductor.

PN	Max. Conductor resistance, 20°C (Ω/km)	Nom. Insulation thickness (mm)	Min. Sheath thickness (mm)	Approx. Overall Diameter, (mm)
PW2XHK-S2-2C1.5mm2-X	13.3	0.7	0.75	8.9
PW2XHK-S2-2C2.5mm2-X	7.98	0.7	0.75	9.8
PW2XHK-S2-2C4mm2-X	4.95	0.7	0.92	11.2
PW2XHK-S2-2C6mm2-X	3.30	0.7	0.92	12.3
PW2XHK-S2-2C10mm2-X	1.91	0.7	1.09	15.7
PW2XHK-S2-2C16mm2-X	1.21	0.7	1.09	17.5
PW2XHK-S2-2C25mm2-X	0.78	0.9	1.09	21.3
PW2XHK-S2-2C35mm2-X	0.554	0.9	1.26	23.9

Technical data

Rated voltage	0.6/1 kV
Dielectric Strength	AC 3500V, 5min, no breakdown
Rated operating temperature range	-15°C ~ +90°C
RoHS	Compliant
Flame retardant	IEC 60332-1-2
Halogen free	IEC 60754-1, IEC 60754-2
Low smoke	IEC 61034-2

Marking on cable

PROSE _ PW2XHK-S2-2CXXmm2-X _ _ _ _ (DD+MM+SS+YY+NNNNN) _ _ _ _ XXXXm
Remark1: Printing Interval: 1m, within ±0.5% accuracy.
Remark2: PW2XHK-S2-2CXXmm2-X means the product number, and the PN in the actual order shall prevail.
Remark3: (DD+MM+SS+YY+NNNNN) means cable code.
Remark4: XXXXm means cable meter.

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.