

Main Features

- Support up to 8 channels of SISO or MIMO for any band's configuration in band 1/3/7/20/28/41/n77
- Support 2G/3G/4G/5G technologies
- Suitable for large-scale indoor installations / Neutral Host / Multi-Operator applications
- Hybrid DC/Fiber Feed for plug and play installation
- Features remote-control and monitoring



Electrical Specifications

		Uplink	Downlink
Frequency	Band 1 (2x2 MIMO)	1920 - 1980 MHz	2110 - 2170 MHz
	Band 3 (2x2 MIMO)	1710 - 1785 MHz	1805 - 1880 MHz
	Band 7 (2x2 MIMO)	2500 - 2570 MHz	2620 - 2690 MHz
	Band 20 (2x2 MIMO)	832 - 862 MHz	791 - 821 MHz
	Band 28 (2x2 MIMO)	703 - 748 MHz	758 - 803 MHz
	Band 41/n41 (2x2 MIMO)	2496 - 2690 MHz	2496 - 2690 MHz
	n77 (4x4 MIMO)	3300 - 4000 MHz	3300 - 4000 MHz
Gain	Band 20/28	28 ± 2 dB	28 ± 2 dB
	Band 1/3/7/41	31 ± 2 dB	31 ± 2 dB
	n77	34 ± 2 dB	34 ± 2 dB
Low Power system RF output power	Band 20/28	---	21 ± 1 dBm (RF per band per port)
	Band 1/3/7/41	---	24 ± 1 dBm (RF per band per port)
	n77	---	27 ± 1 dBm (RF per band per port)
Impedance		50 Ω	50 Ω

Environmental Specifications

Operating temperature range	-10 °C to +40 °C
Storage temperature range	-40°C to +85°C
Relative humidity	5% - 98%
Ingress protection	IP30

Mechanical Specifications

Dimensions	1200 x 800 x 600 mm
------------	---------------------

Configuration List

PN	QTY	Remark
DBU-Card-20-Q77-N-SF-D-01	1	
DBU-Card-20-D1-LN-SF-D-01	1	
DBU-Card-20-D3-LN-SF-D-01	1	
CAB-DBU-D-01	1	
PBMU-N30-D1D3D8D20D28D41Q77-40R32F-30	1	
NEU-4F32F-16	1	
CU-8-WB-64F-10	1	
19' Cabinet	1	

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.